

64K CMOS Static RAM (16384×4) 22PIN 7188

型名	社名	温度範囲 (°C)	スイッチング特性											電 源			入力[*typ]			出力[*typ]			備 考
			TAAC max (ns)	TCAC max (ns)	T _{OE} max (ns)	T _{OH} min (ns)	T _{OD} max (ns)	T _{WP} min (ns)	T _{DS} min (ns)	T _{DH} min (ns)	T _{WD} min (ns)	T _{WR} max (ns)	VDD or VCC (V)	I _{DD} max (mA)	I _{DD} STANDBY (I _{SB} /I _{SB2}) (mA)	V _{IL} max (V)	V _{IH} min (V)	C _i max (pF)	V _{OL} /V _{OH} max/min (V/mA)	V _{OH} /V _{IH} min (V/mA)	C _o max (pF)		
51C98-20	INTEL	0~70	20	20		3	15	15	12	0	2	4.5~5.5	100		15/-	0.8	2.2	7	0.4/8	2.4/4	7		
51C98-25	INTEL	0~70	25	25		3	15	20	15	0	2	4.5~5.5	100		15/-	0.8	2.2	7	0.4/8	2.4/4	7		
51C98-30	INTEL	0~70	30	30		3	20	20	15	0	2	4.5~5.5	100		15/-	0.8	2.2	7	0.4/8	2.4/4	7		
Am99C164-25	AMD	0~70	25	25			20	20	15	0	5	4.5~5.5	110		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
Am99C164-35	AMD	0~70	35	35			20	30	20	0	5	4.5~5.5	110		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
Am99C164-45	AMD	0~70	45	45			20	40	25	0	0	4.5~5.5	110		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
Am99C164-55	AMD	0~70	55	55			25	50	30	0	0	4.5~5.5	110		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
Am99C164-70	AMD	0~70	70	70			25	65	40	0	0	4.5~5.5	110		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CAT71C88-45	CATALYST	0~70	45	45		5	25	40	25	0	5	4.5~5.5	110		30/2	0.8	2.2	6	0.4/8	2.4/4	8		
CAT71C88-55	CATALYST	0~70	55	55		5	25	45	25	0	10	4.5~5.5	110		30/2	0.8	2.2	6	0.4/8	2.4/4	8		
CAT71C88-70	CATALYST	0~70	70	70		5	30	55	30	0	15	4.5~5.5	110		30/2	0.8	2.2	6	0.4/8	2.4/4	8		
CXK5464AP-25L	SONY	0~70	25	5		3	15	20	10	0	0	4.5~5.5	85		25/0.01	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464AP-30L	SONY	0~70	30	5		5	15	25	15	0	0	4.5~5.5	85		25/0.01	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464AP-35L	SONY	0~70	35	5		5	15	30	15	0	0	4.5~5.5	85		25/0.01	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-45	SONY	0~70	45		5	20	35	20	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-45L	SONY	0~70	45		5	20	35	20	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-55	SONY	0~70	55		5	20	45	25	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-55L	SONY	0~70	55		5	20	45	25	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-70	SONY	0~70	70		5	20	55	30	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CXK5464P-70L	SONY	0~70	70		5	20	55	30	0	0	0	4.5~5.5	90		25/-	0.8	2.2	7	0.4/8	2.4/4	7		
CY7C164-10VC/LC	CYPRESS	0~70	10	10	8		8	8	8	0	0	4.5~5.5	125			0.8	2.2	5	0.4/8.0	2.4/4.0	7		
CY7C164-20	CYPRESS	0~70	20	10	3		8	15	10	0	0	4.5~5.5	80		40/20	0.8	2.2	5	0.4/8.0	2.4/4.0	7		
CY7C164-25	CYPRESS	0~70	25	12	3		10	15	10	0	0	4.5~5.5	70		20/20	0.8	2.2	5	0.4/8.0	2.4/4.0	7		
CY7C164-35	CYPRESS	0~70	35	15	3		15	20	15	0	0	4.5~5.5	70		20/20	0.8	2.2	5	0.4/8.0	2.4/4.0	7		
CY7C164-45	CYPRESS	0~70	45	20	3		15	20	15	0	0	4.5~5.5	50		20/20	0.8	2.2	5	0.4/8.0	2.4/4.0	7		
HM6288LJP-25	HITACHI	0~70	25	25		3	12	20	12	0	0	4.5~5.5	120		30/0.1	0.8	2.2	6	0.4/8	2.4/4.0	8		
HM6288LJP-35	HITACHI	0~70	35	35		5	20	30	20	0	0	4.5~5.5	120		30/0.1	0.8	2.2	6	0.4/8	2.4/4.0	8		
HM6288P-35	HITACHI	0~70	35		5	20	30	20	0	5		4.5~5.5				0.8	2.2	6	0.4/8	2.4/4	10		
HM6288P-45	HITACHI	0~70	45		5	20	40	20	0	5		4.5~5.5				0.8	2.2	6	0.4/8	2.4/4	10		
HM6288P-55	HITACHI	0~70	55		5	20	50	25	0	5		4.5~5.5				0.8	2.2	6	0.4/8	2.4/4	10		
HM6288P/JJP-25	HITACHI	0~70	25	25		3	12	20	12	0	0	4.5~5.5	120		30/2.0	0.8	2.2	6	0.4/8	2.4/4.0	8		
HM6288P/JJP-35	HITACHI	0~70	35	35		5	20	30	20	0	0	4.5~5.5	120		30/2.0	0.8	2.2	6	0.4/8	2.4/4.0	8		
HM6788HAP-12	HITACHI	0~70	12	12		4	6	8	6	0	1	4.5~5.5	120		30/10	0.8	2.2	6	0.4/8	2.4/4	10		
HM6788HAP-15	HITACHI	0~70	15	15		4	6	10	7	0	1	4.5~5.5	120		30/10	0.8	2.2	6	0.4/8	2.4/4	10		
HM6788HAP-20	HITACHI	0~70	20	20		4	8	13	10	0	1	4.5~5.5	120		30/10	0.8	2.2	6	0.4/8	2.4/4	10		
HM6788HP-15	HITACHI	0~70	15	15		3	6	10	9	0	1	4.5~5.5	120		30/10	0.8	2.2	6	0.4/8	2.4/4	10		
HM6788HP-20	HITACHI	0~70	20	20		3	8	15	10	0	1	4.5~5.5	120		30/10	0.8	2.2	6	0.4/8	2.4/4	10		
HM6788P-25	HITACHI	0~70	25	25		5	10	20	15	5	0	4.5~5.5	120		30/10	0.8	2.2	6.0	0.5/8	2.4/4	8.0		
HM6788P-30	HITACHI	0~70	30	30		5	12	25	15	5	0	4.5~5.5	120		30/10	0.8	2.2	6.0	0.5/8	2.4/4	8.0		
HY62C88-35	HYUNDAI	0~70	35	35		5	25	25	20	5	0	4.5~5.5	130		20/3	0.8	2.2	5	0.4/8	2.4/4	8		
HY62C88-45	HYUNDAI	0~70	45	45		5	30	30	25	5	0	4.5~5.5	130		20/3	0.8	2.2	5	0.4/8	2.4/4	8		
HY62C88-55	HYUNDAI	0~70	55	55		5	30	35	25	5	0	4.5~5.5	130		20/3	0.8	2.2	5	0.4/8	2.4/4	8		